

Installation Instructions

1. For installation in a vehicle, attach the remote switch bracket to a convenient location on the underside of dashboard using appropriate screws or bolts (not included). Select a location that will avoid damage or tampering by children. Be certain that the terminals on the back of the bracket can not come in contact with any metal objects.
2. Feed the two wires through any convenient access hole and along the underside of the vehicle to the winch. It may be necessary to remove the wires from the back of the switch bracket. Fasten the wires to the vehicle undercarriage securely, without slack using existing clamps or brackets. Keep wires away from hot or moving parts. If wires were previously removed from bracket, reinstall them, making sure wire marked top is on top terminal.
3. Install the switch received with the winch into the vehicle cab and run the wires to the battery following the instructions received with the winch. Shorten the wires as needed to minimize excess length.
4. Push the remote kit plug into the pocket in the winch housing. This may be a tight fit and wiggling while inserting and removing will help. The wire marked "Top" must be toward the top of the winch.
5. To operate winch, install switch in pocket and rotate as indicated. Because the winch may be out of view from the operator, it is recommended that a second person be positioned as an observer to avoid tangled cable or winch overload. When winching is complete remove switch from bracket and store in another location.
6. The winch can be removed for storage by removing the plug from the pocket in the winch. When disconnected, protect the plug from dirt and damage.

Warning:

This switch kit is not for hand held use.

Remove switch from bracket when not in use.