

NEW DLx PULLING WINCHES

Building on the original DLx winches introduced earlier, the new fully-covered (FC) models take it to an even higher level.

A three-piece cover provides a more streamlined look and protects interior components, while an all-black handle and covered ratchet pawl complete the look.

Five sizes are available, including a 2-speed 2600 lb model.

3-piece high-impact cover with removable hinged top section

Black plated handle with premium cushioned grip

Covered ratchet pawl

Winch strap with hook installed

DLx1900FC



DLx1200FC



DLx2600FC

Shown with top cover open



DLx1200



DLx2300



DLx Winch Specs	Model	Rated Capacity (1)	Drum Hub Dia.	Gear Ratio	Handle Length	Max Mech. Adv.	Maximum Drum Capacity	
							Cable (2)	Strap
	DLx1200 DLx1200FC	1200 lb/544 kg	7/8"	4.4:1	7"	56	7/32" x 56'	31'
	DLx1500 DLx1500FC	1500 lb/680 kg	7/8"	4.4:1	9-1/2"	74	1/4" x 40'	31'
	DLx1900 DLx1900FC	1900 lb/862 kg	1-1/8"	5.4:1	9-1/2"	73	9/32" x 49'	38'
	DLx2300 DLx2300FC	2300 lb/1043 kg	1-1/8"	7.2:1	9-1/2"	95	5/16" x 39'	38'
	DLx2600FC	2600 lb/1179 kg	1-1/8"	17.3:1 / 5.4:1	9-1/2"	229	5/16" x 39'	38'

(1) Capacity based on direct line pull on the third layer of line on the drum. Capacity is reduced as the line builds up on the drum.

(2) Drum capacity based on cable size listed. (Cable not included.) Cable size listed may be too large to be practical for some applications.